



World Conference on Transport Research - WCTR 2019 Mumbai 26-31 May 2019

Controlling Signalized Intersections using Machine Learning

Andreas Berre Eriksen^a, Harry Lahrmann^{b*}, Kim Guldstrand Larsen^a, Jakob Haahr
Taankvist^a

^a Department of Computer Science, Aalborg University, Selma Lagerlöfs Vej 300, DK-9220 Aalborg East, Denmark

^b Department of Civil Engineering, Aalborg University, Thomas Maans Vej 23, DK-9220 Aalborg East, Denmark

Abstract

In Uppaal Stratego for Intelligent Traffic Lights, Eriksen et. al. showed that there is a great optimization potential in using better control algorithms, which optimize the traffic flow based on the radar inputs for a single isolated crossing. The work presented in this paper, show the effect of deploying a similar controller in four signal-controlled intersections on the same road segment, our controller is fully distributed meaning there is no direct coordination between the intersections. Our controller is tested against the real controller deployed in the intersections, currently three of the intersections are coordinated and the last one is traffic controlled. The controllers have been tested using the micro simulation program VISSIM. The simulation shows that in comparison with the existing controller, this controller provides a reduction of between 30% and 50% in average delays, queues and number of stops. The fuel consumption and total travel time of cars in the coordinated section are reduced by about 20% in the simulation study. All these reductions are achieved without making the situation worse for the side roads.

© 2018 The Authors. Published by Elsevier B.V.

Peer-review under responsibility of WORLD CONFERENCE ON TRANSPORT RESEARCH SOCIETY.

Keywords: Signalized Intersections, optimization, Machine Learning, Reinforcement Learning, model checking, Uppaal Stratego;

1. Introduction

Signal-controlled intersections are necessary to maintain good traffic performance and a high safety level on our roads, but signal systems also generate several inconveniences for the road users and society in general. These include operation and maintenance costs, stops in the traffic, increases in delays and high fuel consumption. The issues caused

* Corresponding author. Tel.: +45 4056 0375

E-mail address: hsl@civil.aau.dk

by signal systems largely depend on the control system used [Lauritzen, 1994]. In Denmark, it is estimated that the annual societal costs of a signal-controlled intersection amount to EUR 650,000 of which delay related costs represent 69% of this 2012 [Vejdirektoratet, 2012]. Therefore, signal-controlled intersections represent a great potential for optimizing traffic flows.

A signal controlled intersection can be either time or traffic controlled. In addition, the system can be independent of other intersections or coordinated with other intersections and the coordination can be simple or advanced – often called adaptive signal management [Gautier, 2001]. The first adaptive signal systems were developed in the late 1970s and have since been further developed and new systems have been developed. SCOOT and SCATS are the most common, and together they cover 80% of the market, but there are also systems such as SPOT and MOTION. Common to the systems is that they are based on historical data or feedback from loops. Depending on the system, changes in program, cycle length or offset time typically take one or more minutes, and in some cases, up to 10 minutes. [Kronborg & Davidsson, 2004; Lauritzen, 1994].

Reliable detection of traffic is important and detection can be carried out using many different detection methods. Induction loops detects traffic in point and has always been the most widely used technology, but in recent years traffic radar has become commonplace. The radar technology introduces the so-called Estimated Time of Arrival (ETA) function, which continuously estimates the arrival time of cars to the stop line based on course, speed and position. Most of today's systems do not use the continuous flow of ETA values from the radar, instead they emulate virtual induction loops and thus translate the continuous flow of ETA values into discrete observations of ETA when cars pass a virtual loop. [Jakobsen, 2015; Kildebogaard, 2015; Traffic Rader | Intersection Management, 2016]. Today's control of signal systems builds on a few simple signal controlling principles. Typical elements are predetermined phase order fixed offset times, fixed maximum cycle times, and fixed maximum and minimum green times. Even no binding regulation applies to these control elements strong traditions seems to influence the choice of values to be used.

The starting point for this project is to use modern optimization techniques to optimize traffic flow in signal controlled intersections. Others have done this before and examples of this are: [Mousavi, 2017] views traffic in intersections as MDP with Reinforcement Learning and Deep Policy-Gradient and train a deep neural network for adaptive signal control. The resulting controller was evaluated on a small example with respect to different metrics using synthetic traffic load. No comparison to existing controllers were made, nor does the paper evaluate with respect to actual traffic. [Genders 2016] use Q-learning use for off-line training deep neural networks representation of traffic light control policies for different optimization criteria. The resulting controllers are experimentally evaluation using the simulation tool SUMO on a small synthetic intersection. [El-Tantawy 2013] presents an extensive comparison of different off-line learning methods (Q-learning, SARSA, TD) for traffic control based on MDP models based on evaluation of different traffic scenarios from Toronto. [Balaji 2010] applies Q-learning to *off-line* optimize green timing in an urban arterial road network to reduce total travel time. The method was tested on simulation of traffic in highly congested section of the Central Business District area in Singapore. [Sanchez-Medina 2010] use genetic algorithms and cellular-automata-based simulators for *off-line* training optimal traffic signal control. The resulting controller was tested on simulation of contested scenarios for “La Almozara” in Saragossa, Spain.

This project is based on [Eriksen, 2017] which use Uppaal Stratego for *online* synthesis of optimal control for a signal controlled intersection. Uppaal Stratego is an optimization program that combines machine learning and model checking techniques to synthesize at run-time a near-optimal control strategy for signal management [David, 2015]. Importantly, and in contrast to above-mentioned applications of Reinforcement Learning to signal controlling, there is no training phase (say for training a Neural Network). In fact, our method will immediately adapt to any changes in the pattern of traffic, and will allow instantaneous change of optimization criteria. We use as a case a road segment from Hobrovej, Aalborg with four signal controlled intersections. The aim of the project is to develop a new controller based on real time optimization of the signal setting from continuous radar information, with a minimum of restrictions on phase order and minimum/maximum green times. For evaluation we compare the difference between the existing controller and the new controller.

2. Method

The project is based on a section in the street Hobrovej in Aalborg, Denmark, which has six signal-controlled intersections, see Figure 1. The route is an important entry road to the city of Aalborg and has an AADT of 20,000–30,000 vehicles [Mastra, 2017]. Moreover, three of the intersections are coordinated in a green wave with partial traffic management. The optimization is investigated only in the middle four signal-controlled intersections, while the northern and southern intersections are simply used to model traffic correctly in the simulation program.



Figure 1 - The six signal controlled intersections in the street Hobrovej and the distance between the intersections. © OpenStreetMap contributors.

2.1. Traffic modelling

The project uses the VISSIM microsimulation program. This program allows modelling traffic, thus enabling comparing traffic flow with the current controller and the controller developed in this project. VISSIM is used to measure delays, queue lengths, number of stops, fuel consumption and total traveling time on the main road. [PTV VISSIM, 2017].

2.2. Data Collection and Processing

As input to VISSIM we used intersection counts from all six intersections in the morning peak hours from 7:00 to 9:00. The counts were made in 15-minute intervals. Pedestrians and cyclists are not included in this project.

2.3. The Controller

In the paper we have developed a controller, which optimizes the signal setting based on reinforcement learning using continuous input information about all cars within 200 meters of the intersections stop line. The control strategy is synthesised using the software Uppaal Stratego [David, 2015]. We used the micro simulation tool VISSIM to generate the input traffic and evaluate the effect of the control strategy. In this we only use a single optimization criterion namely the overall delay in each of the four crossings, we will see later in the results that even though we only optimize for average delay the derived effects on all measures are positive.

Data equivalent to radar data is extracted from VISSIM through the COM-interface, which is available in the programming language Python, see Figure 2. The data is filtered and partitioned into four subparts one for each intersection. For each intersection we track the ETA (Estimated Time of Arrival) of all cars within 200 meters of the intersection each second. We then run Uppaal Stratego for each intersection with the car information and signal setting that belongs to that intersection. Uppaal Stratego uses this data to generate build an abstract MDP model from which a near-optimal signal setting for the intersection. is then generated. The signal setting is then read in Python and effectuated in VISSIM. This communication pattern is repeated each second.




Figure 2 - The communication between Vissim, Python and Uppaal Stratego.

The control of each intersection is performed in a distributed manner meaning that there is no communication or coordination between any of the intersection. In Uppaal Stratego we can optimize for any number of parameters, for example queue length, number of stops and delay. In this paper the signal setting is optimized to minimize the overall delay of all cars.

2.4. The Uppaal Stratego Controller

The optimal signal setting is decided *on-the-fly* using the optimization tool Uppaal Stratego: Every second an abstract (MDP) model is initialized using the current traffic situation in the intersection. The information used to make the model are the vehicles detected by the radars, as well as estimates of how well the traffic is moving based on the previous traffic. As an example, we model and optimize a simplified intersection seen in Figure 3 in Uppaal Stratego: This intersection only has two lanes one from East to West and one from South to North. In the current situation, 4 vehicles are waiting from East and 2 from South. Based on previous traffic, the arrivals of vehicles from both East and South are assumed to be exponentially distributed with rates 1, i.e. $r_S = r_E = 1$. In the current situation, the signal setting is green from east to west.

We also have parameters in the model describing how fast the traffic moves away from the intersection. Here the rates of this model are $r_W = -4$ ($r_N = -5$), meaning that when the signal is green in East-West direction (South-North direction) the traffic moves away from the intersection at these rates.




Figure 3 – Overview of the example crossing.




Figure 4 - Example of an MDP. (x,y) indicates the configuration with x cars waiting from East and y cars waiting from South.

The signal setting may be changed every second and the underlying mathematical model is a Markov Decision Process (MDP) [Puterman, 1994]. An MDP is illustrated in Figure 4. As we know our current configuration at time $T = i$, we will have a distribution of states we can end up in depending on the choice we make. Our choices in this model is to extend green time or give green to the other direction. Faced with this MDP we can now find an optimal control strategy, which optimizes the objective the model is given. E.g. total delay of all vehicles. To solve the problem, we use Reinforcement Learning which performs an iterative simulation of the MDP-model with the goal to learn the optimal control strategy. We model the choice of phases in Uppaal Stratego using a state machine augmented with timing constraints, expressed using limitations on local clocks (a so-called timed automata). This enables us to guarantee things like minimal green times. In the state machine in Figure 5 x is a local clock, which is reset every time we change the signal setting. The test $x \geq 4$ ensures that we only change the setting after four or more seconds. If this test is replaced by the constraint $x == 4$, then we describe a time controlled system where the setting is changed after exactly four seconds. The test $y == 1$ on the local clock y ensures that phase changes may take place every second.




Figure 5 – Uppaal Stratego model of the intersection seen in Figure 3.




Figure 6 – A simulation of the example intersection using a time controlled system.

In Figure 6, we see a simulation in Uppaal Stratego of a time controlled system over 100 seconds. In the figure we see the two queue lengths as functions of time and the blue curve shows (as 0 or 1) the signal setting. As we see the setting changes after exactly four seconds. An estimate of the accumulated total queue length over 100 seconds is 1411 ± 42.38 .

For comparison, we show in Figure 7 a simulation of a trained optimal control strategy. As we can see the system is not time controlled, but controlled by the actual traffic in the system. An estimate of the total queue length over 100 seconds is 829 ± 14.57 which means a reduction of 41%.

Above we calculated (learned) the optimal signal setting using Uppaal Stratego based on a model of a snapshot of the intersection, which means we only have information on the vehicles up to 200 meters from the crossing. It is clear that the situation can change significantly in a given horizon (e.g. 20 or 100 seconds). This means that more or less vehicles than expected compared to the assumptions could arrive in the crossing. To combat this problem we introduce a rolling horizon. The rolling horizon gives the opportunity to continuously adapt the model and by that the signal setting to the actual traffic, see Figure 8. This means the decision about the signal setting will be updated once every second.




Figure 7 – A simulation of the example intersection using a learned optimal controller.

3. Results




Figure 8 – We learn a strategy up to a horizon, we then after a second learn a new strategy using the updated information from the radar.

The effect of the new controller is documented by comparing the simulation results from the existing controller with the simulation results from the new controller. The evaluation measures the average delay, mileage, fuel consumption and number of stops made in the individual intersection. In addition, the total travel time at Hobrovej is also measured see Figure 1. Detailed data for the individual traffic flows are presented for the intersection Hobrovej/Ny Kærvej/Vestre Allé, this is the largest of the intersections, see Figure 2.

We see on Figure 9 that the new controller has a significant effect for all the measured parameters. The average delay is reduced between 27 % and 54 %, the queue lengths are reduced 42-64 %, the number of stops 20-59 % and the fuel consumption 19-28 %. In addition to this the total travel time for the whole segment of Hobrovej is reduced by 29% and 16% for respectively the north and south bound directions.




Figure 9 – Summarized results for all intersections. The graph shows the percentwise reduction in the measures using the new controller.

Table 1 Average delay in the respective legs with existing controller and new controller, as well as the absolute and relative effects for the intersection of Hobrovej/Ny Kærvej/Vestre Allé.

Average delay		(Hobrovej/Ny Kærvej/Vestre Allé)				
Traffic flow		Existing controller	New controller	Number	Effect	
From	To	[sec./veh.]	[sec./veh.]	[veh.]	[sec./veh.]	[%]
Hobrovej S	Hobrovej N	14	5	1819	-8	-60
Ny Kærvej	Vestre Allé	30	16	340	-14	-46
Ny Kærvej	Hobrovej S	35	22	174	-13	-36
Vestre Allé	Ny Kærvej	46	17	411	-28	-63
Vestre Allé	Hobrovej S	48	14	139	-34	-71
Vestre Allé	Hobrovej N	50	27	147	-23	-46
Ny Kærvej	Hobrovej N	29	15	333	-15	-50
Hobrovej S	Ny Kærvej	13	5	290	-9	-65
Hobrovej S	Vestre Allé	21	13	159	-8	-37
Hobrovej N	Ny Kærvej	26	18	252	-8	-31
Hobrovej N	Vestre Allé	9	5	95	-5	-50
Hobrovej N	Hobrovej S	9	5	1,337	-5	-49
Weighted average		20	9	5,495	-11	-53

From Table 1 we observe that the controller reduces the average delay for all directions. This shows that the controller can exploit the observed flow of the traffic better than existing controllers. This means the new controller has reduced the average delay for all streams, and that it does not just move capacity from the side roads to the main road.

To capture the new controller's performance with respect to the green wave the travel time on the main road is captured for both controllers this is shown in Figures 10 and 11.

The results shows that the highest performance difference is when the congestion is at its highest. This result shows that the new controller is able to constantly avoid being in a state where the intersection is fully congested.




Figure 110 – The north bound travel time




Figure 10 – The north bound travel time

4. Discussion and Conclusion

Through microsimulation with VISSIM, we have demonstrated that a new Uppaal Stratego based controller makes traffic significantly more effective than the existing controller for the metrics average delay, queue length, number of stops, fuel consumption and overall travel time. All parameters were improved in the four intersections and in addition, the total travel time in the previously coordinated route was also significantly improved. The controller reduces the measured parameters for all streams, it does not just move capacity from the side roads to the main direction.

As mentioned earlier, in this project, we only use a single optimization criterion, the overall delay in each of the four crossings. However, with the methods we have used, we can include any other measurable criteria in the optimization - for example a criterion that the queue length in a turning lane must not exceed the length of the turning lane. Another example could be to prioritize the public transport in the optimization, and even include the number of passengers in the bus in the optimization. It is also possible work with dynamic constraints in the optimization, for example, that the maximum red time depends on traffic density so that it rises when traffic rises.

5. References

1. Balaji, P.G.; German, X.; Srinivasan, D.: 'Urban traffic signal control using reinforcement learning agents', *IET Intelligent Transport Systems*, 2010, 4, (3), p. 177-188, DOI: 10.1049/iet-its.2009.0096
2. David A, Jensen PG, Larsen KG, Mikučionis M and Taankvist JH 2015, Uppaal Stratego. *21st International Conference on Tools and Algorithms for the Construction and Analysis of Systems (TACAS)*.
3. Samah El-Tantawy, Baher Abdulhai & Hossam Abdelgawad (2013): Design of Reinforcement Learning Parameters for Seamless Application of Adaptive Traffic Signal Control, *Journal of Intelligent Transportation Systems: Technology, Planning, and Operations*, DOI: 10.1080/15472450.2013.810991
4. Eriksen AB, Huang C, Kildebogaard J, Lahrmann H, Larsen KG, Muniz M & Taankvist JH, 2017, Uppaal Stratego for Intelligent Traffic Lights, *12th ITS European Congress*, Strasbourg, France, 19-22 June 2017.
5. Gautier, E 2001, Adaptive signalsystemer. *Dansk Vejtidskrift (now Trafik & Veje)*, maj 2001, pp 36-37.
6. Genders, W., & Razavi, S. (2016). Using a Deep Reinforcement Learning Agent for Traffic Signal Control. *CoRR*, abs/1611.01142.
7. Jakobsen, L. 2015, Intelligent detektering i trafiksignaler. *Webinar, ITSDanmark*, http://itsdanmark.dk/_files/2015020515.02intelligentedetkteringitrafiksignaler.wmv, Accessed 2. april 2017.
8. Kildebogaard, J. 2015, Trafiksignaler - hvordan udnytter vi udviklingspotentialer? *Trafik & Veje*, september 2015, side 28-30.
9. Kronborg, P. & Davidsson, F. 2004, *Adaptiv styrning av Stockholms trafiksignaler*, *Kunskapsammanställning och förslag*, Movea Trafikkonsult AB.
10. Lauritzen 1994, "Signalregulerede kryds" i *Vejtrafik – Trafikteknik & Trafikplanlægning*, Lahrmann, H. & Leleur, S., Polyteknisk Forlag. Side 147-180.
11. Mastra 2017, www.kmastra.dk, Accessed 5 December 2017
12. Puterman M.L. 1994, *Markov Decision Processes*. Wiley and Sons, 1994.
13. Mousavi, Seyed Sajad; Schukat, Michael; Howley, Enda: 'Traffic light control using deep policy-gradient and value-function-based reinforcement learning', *IET Intelligent Transport Systems*, 2017, 11, (7), p. 417-423, DOI: 10.1049/iet-its.2017.0153
14. PTV VISSIM 2017, <http://vision-traffic.ptvgroup.com/en-us/products/ptv-vissim/>, Accessed 5 December 2017.
15. Traffic Rader|Intersection Management, 2016, Smartmicro, <http://www.smartmicro.de/traffiradar/intersection-management/>, Accessed 4 April 2017.
16. Vejdirektoratet, 2012. *Konsekvenser for trafikanter og samfund – Bedre trafiksignaler*, København.